



AX-582B

Ψηφιακό πολύμετρο LCD 3.5 digit, 28mm, 3x/s, 3V, 97x35x189mm.

- Measurement: transistors' gain hFE, AC voltage, DC voltage, capacitance, AC current, DC current, resistance
- Kind of display used: LCD 3,5 digit 28mm
- Sampling: 3x/s
- DC voltage measuring range: 0,1m...200m/2/20/200/1000V
- DC voltage measuring accuracy: $\pm(0,5\% + 3 \text{ digits})$
- AC voltage measuring range: 1m...2/20/200/750V
- AC voltage measuring accuracy: $\pm(0,8\% + 5 \text{ digits})$
- Bandwidth for AC voltage measurements: 40Hz...200Hz
- DC current measuring range: 0,1?...200?/20?/20m/200m/2/20A
- DC current measuring accuracy: $\pm(0,8\% + 4 \text{ digits})$
- AC current measuring range: 0,1m...200m/2/20A
- AC current measuring accuracy: $\pm(2\% + 5 \text{ digits})$
- Bandwidth for AC current measurements: 40Hz...200Hz
- Resistance measuring range: 0,1...200/2k/20k/200k/2M/200M Ω
- Resistance measuring accuracy: $\pm(0,8\% + 3 \text{ digits})$
- Capacitance measuring range: 10p...20n/2?/200?F
- Capacitance measuring accuracy: $\pm(2,5\% + 20 \text{ digits})$
- Diode test: 1mA, 3V
- Transistors' gain (hFE) test: 3V
- Continuity test: acoustic signal for $R < 70\Omega$
- Overall dimensions (W x D x H): 97 x 35 x 189mm
- Weight with battery: 375g
- Power supply: 1 battery 9V 6F22, set without battery
- Optional equipment: AX-58P soft cover
- Conform to the norm: EN61010 600V CAT IV

Measuring instrument features

- automatic power-off
- HOLD function
- impact resistant holster
- manual ranging
- universal
- detects line wire (acoustic and optical indication)
- low battery indicator