



AX-100

Ψηφιακό πολύμετρο, LCD 3,5 digit (1999), 3x/s, 0~40° C

- Measurement: AC voltage, DC voltage, DC current, resistance
- Kind of display used: LCD 3,5 digit (1999)
- Sampling: 3x/s
- DC voltage measuring range: 100m...200m/2/20/200/600V
- DC voltage measuring accuracy: $\pm(0,5\% + 4 \text{ digits})$
- AC voltage measuring range: 100m...200/600V
- AC voltage measuring accuracy: $\pm(1,2\% + 10 \text{ digits})$
- DC current measuring range: 1m...20u/200u/2m/20m/200m/10A
- DC current measuring accuracy: $\pm(1,5\% + 3 \text{ digits})$
- Resistance measuring range: 0,1Ω...200Ω/2kΩ/20kΩ/200kΩ/20MΩ
- Resistance measuring accuracy: $\pm(0,8\% + 5 \text{ digits})$
- Diode test: 1mA, 3V
- Continuity test: acoustic signal for $R < 70\Omega$
- Operating temperature: 0...40° C
- Overall dimensions (W x D x H): 85 x 30 x 145mm
- Weight with battery: 170g
- Power supply: 1 battery 9V 6F22, set without battery
- Standard equipment: test leads

Measuring instrument features

- shock-resistant case
- manual ranging
- low battery indicator
- Gross weight: 0.24 kg