



AX-572

AX-572 Ψηφιακό πολύμετρο LCD 3,5 ψηφίων με καπασιτομετρο 20mF

- Measurement: transistors' gain hFE, AC voltage, DC voltage, capacitance, AC current, DC current, resistance
- Sampling: 3x/s
- DC voltage measuring range: 100m...200m/2/20/200/1000V
- DC voltage measuring accuracy: $\pm(0,5\% + 3 \text{ digits})$
- AC voltage measuring range: 1m...2/20/200/750V
- AC voltage measuring accuracy: $\pm(2\% + 5 \text{ digits})$
- DC current measuring range: 0,01m...20m/200m/20A
- DC current measuring accuracy: $\pm(0,8\% + 10 \text{ digits})$
- AC current measuring range: 1m...2m/200m/20A
- AC current measuring accuracy: $\pm(0,8\% + 5 \text{ digits})$
- Resistance measuring range: 0,1...200/2k/20k/200k/2M/20MΩ
- Resistance measuring accuracy: $\pm(0,8\% + 3 \text{ digits})$
- Capacitance measuring range: 20mF
- Capacitance measuring accuracy: $\pm(2,5\% + 20 \text{ digits})$
- Diode test: 1mA, 3V
- Transistors' gain: (hFE) test 3V
- Continuity test: acoustic signal for R up to 70Ω
- Overall dimensions (W x D x H): 93x55x175mm
- Weight: 400g
- Power supply: 1 battery 9V 6F22, set without battery
- Conform to the norm: EN61010 600V CAT III