



## UT203+

Ψηφιακή Αμπεροτσιμπίδα AC/DC Φ28mm με LCD και μέτρηση ρεύματος 400A.

- Manufacturer: UNI-T
- Type of meter: AC/DC digital clamp meter
- Max. diameter of measured cable: 28mm
- Kind of display used: LCD (4000)
- DC current measuring range: 40A/400A
- AC current measuring range: 40A/400A
- DC current measuring accuracy:  $\pm(2,5\% + 5 \text{ digits})$
- AC current measuring accuracy:  $\pm(2,5\% + 5 \text{ digits})$
- DC voltage measuring range: 400mV/4V/40V/400V/600V
- DC voltage measuring accuracy:  $\pm(0,5\% + 2 \text{ digits})$
- AC voltage measuring range: 4V/40V/400V/600V
- AC voltage measuring accuracy:  $\pm(0,8\% + 5 \text{ digits})$
- True effective value measurement: True RMS
- Resistance measuring range: 400Ω/4kΩ/40kΩ/400kΩ/40MΩ
- Resistance measuring accuracy:  $\pm(0,8\% + 2 \text{ digits})$
- Frequency measuring range: 10...10MHz
- Duty cycle factor: 0.1...99.9%
- Continuity test: acoustic signal for R smaller than 10Ω
- Diode test: yes
- Pollution degree: 2
- Dimensions: 215x63x36mm
- Weight with battery: 235g
- Power supply: 2 batteries 1,5V LR03 (AAA)
- Measurement: AC current, AC voltage, continuity, DC current, DC voltage, duty cycle, frequency, resistance
- Conform to the norm: EN61010 300V CAT III, EN61010 600V CAT II