



UT139B

Ψηφιακό πολύμετρο LCD(4000) με οπίσθιο φωτισμό TRUE RMS.Περιλαμβάνονται στην συσκευασία θήκη και ακροδέκτες μέτρησης.

- Manufacturer: UNI-T
- Type of meter: digital multimeter
- Measurement: AC current,AC voltage, capacitance, continuity, DC current, DC voltage, duty cycle, frequency, resistance.
- Kind of display used: LCD (4000), with a backlight
- DC voltage measuring range: 40mV/400mV/4V/40V/400V/600V
- DC voltage measuring accuracy: $\pm(0,5\% + 2 \text{ digits})$
- AC voltage measuring range: 40mV/400mV/4V/40V/400V/600V
- AC voltage measuring accuracy: $\pm(0,8\% + 3 \text{ digits})$
- DC current measuring range: 400 μ A/4000 μ A/40mA/400mA/4A/10A
- AC current measuring range: 400 μ A/4000 μ A/40mA/400mA/4A/10A
- DC current measuring accuracy: $\pm(0,7\% + 2 \text{ digits})$
- AC current measuring accuracy: $\pm(1\% + 3 \text{ digits})$
- True effective value measurement: True RMS
- Resistance measuring range: 400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω
- Resistance measuring accuracy: $\pm(0,8\% + 2 \text{ digits})$
- Capacitance measuring range: 10nF/100nF/1000 μ F/10mF
- Capacitance measuring accuracy: $\pm(4\% + 5 \text{ digits})$
- Frequency measuring range: 10...10MHz
- Frequency measuring accuracy: $\pm(0,1\% + 4 \text{ digits})$
- Duty cycle factor: 0.1...99.9%
- Diode test: yes
- Continuity test: acoustic signal for R less than 10 Ω
- Weight: 350g
- Conform to the norm: EN61010 600V CAT III
- Dimensions (W x H x D): 80x170x48mm
- Power: battery R6 AA 1,5V x2
- Gross weight: 543.3 g