



AVcam SR5 TESTER

Φορητή οθόνη (TFT LCD) 3,5" για τη δοκιμή καμερών συστημάτων ασφαλείας, επί τόπου χρήση κατά την διάρκεια της εγκατάστασης. Χαμηλή κατανάλωση μπαταρίας. Επαγγελματική σχεδίαση, εύκολο στη μεταφορά.

- Signal mode: NTSC/PAL (Auto Adjust)
- Display: 3.5" TFT-LCD, 960 x 240 resolution
- LCD adjust: Adjustable brightness, contrast, color of LCD
- Video IN/OUT: 1 channel BNC Input & 1 channel Output
- Power output: DC12V, 1A
- Audio input: 1 channel Audio input
- Communication: RS232, RS422 simplex and RS485
- PTZ Protocol: Pelco-D, Pelco-P; Samsung, Panasonic, LiLin or customized
- Baud Rate: 150,300,600,1200,2400,4800,9600,19200bps
- PTZ address scan: Search up the ID of PTZ camera
- PTZ Data Test: Capture and Analyze the PTZ data sent from controlling device
- Color bar generation: Output 1 channel color bar video signal for testing monitor
- UTP cable test: Test UTP cable connection state and display in the screen. Read the number of the test box.
- Multi-Meter: Voltage, current, resistance and capacitance measuring, continuity tests, diode testing.
- Power Adapter: DC5V, 2A
- Battery: 1 pcs Lithium Ion Polymer Batteries, 3.7V DC3000mAh
- Rechargeable: 4.5 hours recharging time, work for 12 hours
- Low Consumption: Sleeping mode, display battery power state
- Sleeping mode: OFF/5-60mins
- Work Temperature: -30° C ~ 50° C
- Work Humidity: 30% ~ 90%
- Dimension/Weight: 112x189x47 mm / 500g