



## AV-6116R5

DVR 16CH 1080N RT 5 σε 1 (AHD/TVI/CVI/NVR/960H), H 264 dual stream, recording 16CH 1080N RT, playback 16CH 1080N RT, 4 Audio In / 1 Audio Out, 2 Sata HDD, alarm, RS485, USB backup, Έξοδος VGA, HDMI 1080P, CVBS, P2P, SmartPhone support, USB

Channel	Mode Analog channel + Digital channel		Playback
	No	Channel number * Resolution/Frame rate	Channel number * Resolution/Frame rate
16CH	1	16*1080N/25+0	16*1080N/25
	2	12*1080N/25+4*1080P/25	4*1080P/25
	3	8 * 1080N/25 + 8 * 1080P/25	4*1080P/25
	4	4 * 1080N/25 + 12 * 1080P/25	4*1080P/25
	5	0+16*1080P/25	8*1080P/25
	6	0 + 8 * 3M/25	8* 3M/25
	7	0 + 4 * 5M/25	4 * 5M/25

mouse.

- Compressed format: H.264
- Operating System: embedded Linux
- Maximum video Input: 16
- VGA output: Yes
- BNC video output: Yes
- HDMI output: Yes
- Audio in: 4
- Audio out: 1
- Talk: Yes
- Alarm in: 4
- Alarm out: 1
- Maximum Record: 16
- Record type: Regular, Manual, Detect, Alarm
- Maximum Playback: 16
- Playback search ways: Point in time, Calendar, Event, Channel

### Backup

- USB mobile hard disk, U disk: Yes
- USB DVD CD Writer: Yes
- Format: DAV, AVI

### Remote view

- Browser: Many Web browser
- CMS: CMS3.0
- APP: iPhone, Android

### Storage

- HDD number: 2

### PTZ

- Interface: RS485
- Protocol: PELCO P, PELCO D, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
- Control ways: Pan, Tilt, Zoom, Preset, Cruise, Trace

### Network

- Ethernet Interface: 10/100 Mbps Ethernet (RJ-45)
- Protocol: TCP/IP, DHCP, DDNS, NTP, SMTP

### Others

- Power Supply: DC 12V / 6A
- Work Temperature: -10° C ~ +60° C
- Work Humidity: 10% ~ 90%