




序号/No.	名称/Title	文件编号/File No.
1	塑料件	QJ/XYT-11118
2	端子	QJ/XYT-11120



**Specifications:**  
 Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP




**Dielectric Withstanding**  
 Voltage: AC 500V For 1 minute  
 Operating Temperature: -55°C--+105°C  
 Contact: Brass  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

- 要求:**
1. 塑料件无裂痕。
  2. 整排端子成一直线，相邻端子之间相互平行。

设计/Designed by	绘图/Drawn by	审核/Checked by	批准/Approved by	备注/Remarks
新亚联合科技 M&E XINYA UNITED TECH CO.,LTD.				
图名/Title		文件编号/File No.		公差/General Tolerance
112-A 单排直针		QJ/XYT-12020		X: ±0.2 H: ±0.2
产品图		页码/Sheet		Y: ±0.3 L: ±0.1
				W: ±0.05 (not <math>0.5^{\circ}</math>)
				XXX ±0.01
备注/Remark		单位/Units:		MM

序号/No. 更改记录/Revision note 签名/Signature 日期/Date

序号/No.	名称/Title	文件编号/File No.
1	塑料件	QJ/XYT-11118
2	端子	QJ/XYT-11120



**Specifications:**  
 Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP




**Dielectric Withstanding**  
 Voltage: AC 500V For 1 minute  
 Operating Temperature: -55°C--+105°C  
 Contact: Brass  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

- 要求:**
1. 塑料件无裂痕。
  2. 整排端子成一直线，相邻端子之间相互平行。

设计/Designed by	绘图/Drawn by	审核/Checked by	批准/Approved by	备注/Remarks
新亚联合科技 M&E XINYA UNITED TECH CO.,LTD.				
图名/Title		文件编号/File No.		公差/General Tolerance
112-A 单排弯针		QJ/XYT-12024		X: ±0.2 H: ±0.2
产品图		页码/Sheet		Y: ±0.3 L: ±0.1
				W: ±0.05 (not <math>0.5^{\circ}</math>)
				XXX ±0.01
备注/Remark		单位/Units:		MM

序号/No. 更改记录/Revision note 签名/Signature 日期/Date

序号/No.	名称/Title	文件编号/File No.
1	塑料件	QJ/XYT-11119
2	端子	QJ/XYT-11120



**Specifications:**  
 Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP




**Dielectric Withstanding**  
 Voltage: AC 500V For 1 minute  
 Operating Temperature: -55°C--+105°C  
 Contact: Brass  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

- 要求:**
1. 塑料件无裂痕。
  2. 整排端子成一直线，相邻端子之间相互平行。

设计/Designed by	绘图/Drawn by	审核/Checked by	批准/Approved by	备注/Remarks
新亚联合科技 M&E XINYA UNITED TECH CO.,LTD.				
图名/Title		文件编号/File No.		公差/General Tolerance
112-A 双排直针		QJ/XYT-12022		X: ±0.2 H: ±0.2
产品图		页码/Sheet		Y: ±0.3 L: ±0.1
				W: ±0.05 (not <math>0.5^{\circ}</math>)
				XXX ±0.01
备注/Remark		单位/Units:		MM

序号/No. 更改记录/Revision note 签名/Signature 日期/Date

序号/No.	名称/Title	文件编号/File No.
1	塑料件	QJ/XYT-11119
2	端子	QJ/XYT-11120
3	端子	QJ/XYT-11120



**Specifications:**  
 Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP

**Dielectric Withstanding**  
 Voltage: AC 500V For 1 minute  
 Operating Temperature: -55°C--+105°C  
 Contact: Brass  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

- 要求:**
1. 塑料件无裂痕。
  2. 整排端子成一直线，相邻端子之间相互平行。

设计/Designed by	绘图/Drawn by	审核/Checked by	批准/Approved by	备注/Remarks
新亚联合科技 M&E XINYA UNITED TECH CO.,LTD.				
图名/Title		文件编号/File No.		公差/General Tolerance
112-A 双排弯针		QJ/XYT-12026		X: ±0.2 H: ±0.2
产品图		页码/Sheet		Y: ±0.3 L: ±0.1
				W: ±0.05 (not <math>0.5^{\circ}</math>)
				XXX ±0.01
备注/Remark		单位/Units:		MM

序号/No. 更改记录/Revision note 签名/Signature 日期/Date