

SMALL SIGNAL SWITCHING DIODE	REVERSE VOLTAGE - 75 Volts FORWARD CURRENT - 0.15 Amperes
FEATURES ● Silicon epitaxial planar diode ● High speed switching diode ● 500mW power dissipation MECHANICAL DATA ● Case: Mini-MELF glass case ● Polarity: Color band denotes cathode ● Weight : Approx.0.05 grams	DL - 35 Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

MAXIMUM RATINGS

		LL4148	UNIT
Reverse Vltage	V _R	75	V
Peak Reverse Voltage	V _{RM}	100	V
Average Forward Rectified Current Half Wave Rectification with Resist .load at T _{amb} =25°C and f≧ 50Hz	I _O	150	mA
Forward Surge Current at t<1s and T _J =25°C	I _{FSM}	500	mA
Power Dissipation at Tamb=25°C	P _{tot}	500 ⁽¹⁾	mW
Junction Temperature	T _J	175	°C
Storage Temperature Range	T _{STG}	- 65 to + 175	°C

NOTE:(1) Valid provided that electrodes are kept at ambient temperature .

ELECTRICAL CHARACTERISTICS

		MIN	TYP	MAX	UNIT
Forward Voltage at I _F =10mA	V _F	-	-	1	V
Leakage Current at V _R =20V at V _R =75V at V _R =20V T _J =150°C	I _R	-	-	25	nA
	I _R	-	-	5	uA
	I _R	-	-	50	uA
Capacitance at V _F =V _R =0V	C _{tot}	-	-	4	pF
Voltage Rise When Switching ON Tested With 50mA Pulses tp=0.1us.Rise Time<30ns.fp=5to 100Hz	V _{fr}	-	-	2.5	v
Reverse Recovery Time From IF=10mA VR=6V. RL=100Ω at IR=1mA	t _{rr}	-	-	4	ns
Thermal Resistance Junction to Ambient	RθJA	-	-	350 ⁽¹⁾	°C/W
Rectification Efficiency at 100MHZ V _{RF} =2V	η V	0.45	-	-	-

NOTE:(1)Valid provided that electrodes are kept at ambient temperature.

FIG.1-ADMISSIBLE POWER DISSIPATION
VERSUS AMBIENT TEMPERATURE




FIG.2-FORWARD CHARACTERISTICS




FIG.3-ADMISSIBLE REPETITIVE PEAK FORWARD CURRENT VERSUS PULSE DURATION




FIG.4-RECTIFICATION EFFICIENCY MEASUREMENT CIRCUIT




FIG.5-RELATIVE CAPACITANCE VERSUS VOLTAGE




FIG.6-LEAKAGE CURRENT VERSUS JUNCTION TEMPERATURE




FIG.7-DYNAMIC FORWARD RESISTANCE VERSUS FORWARD CURRENT

