

CCTV Tester AG-T104



Seven Essential CCTV Tools

- **Video Displayer**
Display the video from CCTV camera. Technicians can turn the camera position and adjust the lens easily.
- **PTZ Controller**
Control the PTZ (pan/tilt/zoom the PTZ: set and call preset) and search up the ID of the PTZ.
- **UTP Cable Tester**
Test for direct or cross cable, continuity, discontinuity and short on UTP cable.
- **PTZ Protocol Analyzer**
Compatible with over a dozen PTZ protocols to test and program cameras in the field. Decodes and identifies output from PTZ console to aid in troubleshooting.
- **Audio Speaker**
It can be a speaker when input the audio from pickup devices.
- **Camera Power Supply**
Output DC 12V 1A power. It is a perfect power supply for cameras
- **Video Generator**
Generate colorbar to Test video cable and monitor, also check on interference for setting up twisted pair converters and for configuring wireless links.

Aguard CCTV tester—a perfect tool to save time and money

Aguard CCTV tester is an advanced test monitor for CCTV applications, designed to withstand the rigours of daily use. CCTV installers often need to carry a variety of testing tools to complete their work. Aguard CCTV tester combines the most needed tools in one easy-to-carry package. Since all connections (Audio/video/Power /communication) attach to a single unit, Aguard CCTV tester eliminates the need to juggle several devices while on a ladder or lift, making the working conditions safer and increasing productivity.

FEATURES

- 2.8 inch LCD color monitor
- OSD menu operation
- Video signal testing
- Audio speaker
- PTZ controlling
- Camera power supply
- UTP cable testing
- Video signal generating
- RS485 data testing
- 2800mA rechargeable battery power supply
- Multi- protocols compatible: Pelco-D, Pelco-P, Samsung, Panasonic and Molyx.

Aguard CCTV Tester Kits

- Handheld CCTV tester
- 2000mA rechargeable battery
- Power adapter
- BNC video cable
- RCA video cable
- RS485 cable
- RS232 cable
- Power cable
- UTP cable tester
- Safe cord

MODEL	AG-T104
Video Signal Testing	
LCD monitor	2.8 " TFT LCD, 960X240
Signal System	PAL/NTSC
Video Input	1ch(BNC)
Video Output	1ch(BNC)
Video Level	1V p~p
PTZ Controlling	
Communication	RS232, RS422 simplex and RS485
Protocol	Pelco-D, Pelco-P, Samsung, Panasonic and Molyx.
Baud Rate	2400,4800,9600,19200
Other Functions	
UTP Cable Testing	Tests UTP cable connection state and display on the screen
Video Signal Generating	Generates video signal for monitor testing
RS485 Data Testing	Tests the RS485 data from controlling device
Audio Speaker	1ch (RCA)
Camera Power	DC 12V, 1A
General	
External Power Supply	DC 5V
Battery Power Supply	LIP 2800mAh rechargeable battery
Battery Life	11~15 hours working time
Operating Environment	-30°C to 70°C within 90% RH
Dimensions(WXHXD)	170X99X48mm

