

ViPRO D56

Waterproof Dome Camera



- ✓ Waterproof and anti-vandal housing
- ✓ Weather resistant
- ✓ Compact profile
- ✓ Night vision with 24 IR LEDs
- ✓ IR distance: 20 meter
- ✓ High resolution

Technical Specifications

Product series	Waterproof Dome Camera		
	D56-133CI New!	D56-134CI	D56-136CI
Environment Rating	Indoor		
Resolution	1000 TV lines	420 TV lines	420/520/600 TV lines
Sensor	1/3" Sony Color CCD	1/3" Sharp Color CCD	1/3" Sony Super HAD Color CCD
TV System	PAL/NTSC		
Lens	f=2.8mm, F=2.0, f=1.7mm, F=2.9	f=3.6mm F=2.0	3.6mm,4.0mm,6.0mm,8.0mm
Effective pixels	PAL: 960(H) x 576(V) NTSC: 960(H) x 480(V)	PAL: 512(H)*582(V), NTSC: 512(H)*492(V)	PAL: 752(H)*582(V), NTSC: 768(H)*494(V)
Sensing Area	4.8mm*3.84mm	4.9mm(H)*3.7mm(V)	4.9mm(H)*3.7mm(V)
Horizontal Sync. Frequency	15.625KHz/15.734KHz		
Vertical Sync. Frequency	50Hz/60Hz		
Minimum Illumination	0.05Lux(day)/F1.2, 0Lux (with IR on)	0Lux / F1.2 (with IR)	0Lux(IR on)/0.5Lux (day)/F1.2
Scanning System	2:1 Interlace		
Sync System	Internal		
S/N	More than 48dB		
Electronic Shutter	1/50(PAL)~1/100,000 sec, 1/60(NTSC)~100,000 sec	1/50(PAL)~1/10,000 sec, 1/60(NTSC)~10,000 sec	1/50(PAL)~1/100,000 sec, 1/60(NTSC)~100,000 sec
White Balance	Auto		
Auto Gain Control	Auto		
Back Light Compensation	Auto		
Gamma Correction	0.45		
Adjust Angle	120° / 150°	92°	92°
Audio (Microphone)	Optional	Optional	Optional
Video Output	1.0Vp-p composite / 75Ω		
IR	24 IR LEDs		
IR Distance	20 meters		
Power supply	DC 12V		
Current consumption	Max. 300mA		
Working temperature	-20°C~70°C / -4°F~158°F		
Storage temperature	-40°C~80°C / -40°F~176°F		
Working Humidity	RH95% Max.		
Waterproof level	IP67		
Weight	0.45kg / 0.9921lbs		
Size (DxWxH)	Φ93mm x 69mm x 50mm/ Φ0.9" x 1.211" x 1.575"		
Certifications	CE, FCC		