

EX17008A Series

8-port 10/100Base Fast Ethernet Unmanaged PoE Ethernet Switches



Overview

EtherWAN's EX17008A 10/100Base Fast Ethernet Unmanaged PoE Ethernet Switches is designed to operate in the small or medium network environment to provide Power to PoE driven devices, such as PoE IP cameras. The EX17008A may be Desktop or Rack mounted.

All 8 ports on the EX17008A support IEEE802.3af Power over Ethernet (PoE) Power Sourcing Equipment (PSE) and can detect an IEEE802.3af compliant Powered Device (PD). Data and power can be transmitted to a Powered Device (PD) over the same twisted-pair Ethernet cable through any port on the EX17008A.

Features

- Supports IEEE802.3af Power over Ethernet (PoE) Power Sourcing Equipment (PSE)
- Full PoE power supplies on all ports at the same time
- PoE power: 15.4W per port/ 124W per switch
- 1024 MAC addresses
- 512K bits buffer memory
- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- Full wire-speed forwarding rate
- 100 ~ 240VAC, 50~60Hz Internal Universal PSU
- 0°C to 45°C (32°F to 113°F) operating temperature range
- Metal case
- Supports Desktop and Rack Mounting installation

Ordering Information

EX17008A 8-port 10/100Base Fast Ethernet Unmanaged PoE Ethernet Switches

Installation Type: Desktop, Rack mounting kit (optional)

Specifications

Technology

Standards:

- IEEE 802.3af, IEEE802.3 10Base-T, IEEE802.3u 100Base-TX/FX, IEEE802.3x

Forward and Filtering Rate:

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps

Packet Buffer Memory:

- 512K bits

Processing Type:

- Store-and-Forward
- Half-duplex back-pressure and IEEE802.3x full-duplex flow control

Address Table Size:

- 1024 MAC addresses

Power

Input:

- 100 ~ 240VAC, 50~60Hz Internal Universal PSU

Power Consumption:

- 132W Max.

Mechanical

Casing:

- Metal case

Dimensions:

- 266mm (W) x 160mm (D) x 44mm (H)
(10.47" (W) x 6.30" (D) x 1.73" (H))

Weight:

- 1.4Kg (3.08lbs.)

Installation:

- Desktop, Rack Mounting

Interface

Ethernet Port:

- 10/100Base-TX: 8 ports

LED Indicators:

- Per Unit: Power Status
- Per Port: 10/100TX, 100FX: Link/Activity, PoE Act/status

Environment

Operating Temperature:

- 0°C to 45°C (32°F to 113°F)

Storage Temperature:

- -10°C to 70°C (14°F to 158°F)

Ambient Relative Humidity:

- 10% to 95% (non-condensing)

Regulatory Approvals:

ISO:

- Manufactured in an ISO9001 facility

Emission Compliance:

- FCC Part 15, Class A, CE mark Class A

Safety:

- UL60950-1, EN60950-1, IEC60950-1

Diagrams

