

# ViPRO

## RS232 485 Connection Box



**RS232/485 Connection Box** integrate the interface of RS-232, RS-485 and so on, to realize the serial communication between the external device and Mobile Digital Video Record (MVR300 series).



### Key Features

- Two RS-232 interfaces, to connect the automobile station reporter or the other external devices, etc.
- Two RS-485 interfaces, can be use to connect the PTZ or the other external devices, etc.
- Simple wiring
- Overall aesthetic
- Easy maintenance

### Technical Specifications

Product series	RS232/485 wiring box
Series Interface	Two RS-232, Two RS- 485
Power Output	12/2A, 5V/1A
Working Temperature	-30°C~70°C
Storage Temperature	-40°C~85°C
Relative Humidity	≥95%
Cable Length	1000mm
Weight	225g
Dimension	69mm*71mm*21mm
Applied models	MVR 300 series

### Dimension and Definition



- |                                |                                 |
|--------------------------------|---------------------------------|
| 1. GND                         | 9. GND                          |
| 2. Connect peripherals 232 TXD | 10. Connect peripherals 232 TXD |
| 3. Connect peripherals 232 RXD | 11. Connect peripherals 232 RXD |
| 4. DC +12V                     | 12. DC +12V                     |
| 5. DC +5V                      | 13. DC +5V                      |
| 6. Connect peripherals 485A    | 14. Connect peripherals 485B    |
| 7. Connect peripherals 485B    | 15. Connect peripherals 485A    |
| 8. GND                         | 16. GND                         |