



SF1301

Easy Installation & Exceptional Clarity

SF1301W

AVerMedia

AVerDiGi SF1301W/SF1301 High Performance Megapixel Wireless/Wired IP Camera

Key Features

- 1.3 Megapixel resolution delivers crisp and clear images (Up to 1280x1024 resolution)
- UP to 30 fps in VGA (640x480) resolution and 10 fps in SXGA (1280x1024) resolution
- Supports 4 video streams simultaneously with combinations of MJPEG and MPEG4 video formats
- Built-in Omni-directional Microphone
- Universal plug and play
- Using in low light condition - Minimum illumination 0.5 Lux
- Image quality control: Auto White Balance (AWB), Auto Exposure (AE), Auto Gain Control (AGC), Contrast, Saturation and Brightness
- Compatible with AVerDiGi SA/NV/NX/NXU/XR/EH/EXR Series



Bundled with exclusive AVerDiGi Web Browser

AVerDiGi SF1301W/SF1301 High Performance Megapixel Wireless/Wired IP Camera

Specifications


	SF1301W (wireless)	SF1301 (wired)
Model		
Device	1/4 inch CMOS	
Effective Pixels	1280 x 1024	
Min. scene Illumination	0.5 Lux	
F/No	F2.8	
Focus Length	f4.5mm	
Depth	20cm~Infinity	
Viewing Angle	Horizontal:43.6°, Vertical:35.7°, Diagonal:54°	
Motion Detection	Enable/disable; Sensitivity 0~100; Drawing mode - Enable/Disable	
Exposure Control	Auto	
AGC	Yes	
White Balance	Auto	
Compression	MPEG4/MJPEG dual format compression simultaneously	
Multi-profile	Support 4 video streams simultaneously	
Picture Resolution	1280 x 1024; 1024 x 768; 640 x 480; 512 x 384; 320 x 240; 160 x 120	
Bit Rate	IE browser - 900K, 1M, 1.25M, 1.5M, 1.75M, 2M Mobile Video - 64K, 128K, 192K, 256K, 320K, 384K, 448K, 512K	
Image Frame Rate	10 fps at 1280x1024; 30 fps at 640x480	
Black/White mode	Yes	
Digital Zoom	16X	
Mirror	Vertical mirror/Horizontal mirror	
Compression	AMR/ADPCM	
Built-in Microphone	Sensitivity -42dB +/- 3dB (5 Meters distance min.) S/N Ratio:more than 58 dB; Directivity Omni-directional	
Frequency Response	50~16000HZ	
Audio Line Output	Output Line-out For external speaker	
Pre-recording/Post-recording	0~15 seconds/0~15 seconds	
Overwrite	Enable/disable	
Recording mode	Continuous/Event/Motion Detection	
System Log	Up to 500 items stored in flash	
Ethernet	Ethernet (10/100 Mbps Fast) , RJ-45 connector	
Protocol	IPV4, ARP, TCP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTCP, RTSP	
Auto-MDIX	Yes	
3GPP	Audio codec/AMRVideo codec/MPEG4Protocol/RTSP, RTP	
WPS	Yes	No
Web Browser	IE 7.0/FireFox 2.0.7/Safari 3.2.2 or above	
User account	Up to 20 users	
Security	Password protection:configured by the administrator	
Temperature and humidity	-15~60°C (Storage), 90% humidity/0~40°C(Operating), 85% humidity	
Power Consumption	6W (DC 5V)	
Dimensions (W x H x D)	135mm x 169mm x 34mm	
Weight	158 g (w/o bracket)	
Indoor/Outdoor	Indoor	
Bundled accessory	Bracket	

* Specifications subject to change without prior notice

Product Illustration



Product Dimension



Compatible AVerDiGi DVR/NVR

✓ SA Series ✓ NV Series ✓ NX Series ✓ NXU Series ✓ XR Series ✓ EH Series ✓ EXR Series



All right reserved. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means (Electronic, mechanical, photocopy, recording, or otherwise) without the written permission of AVerMedia INFORMATION, Inc. Information in this document is subject to change without notice. The information contained herein, is to be considered for informational purposes only and shall not be considered legally binding. 2008 by AVerMedia INFORMATION, Inc. All rights reserved. No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language in any form by any means without the written permission of AVerMedia INFORMATION, Inc. AVerMedia is registered trademarks of AVerMedia INFORMATION, Inc. All other trademarks belong to their respective companies. Made in Taiwan. 20090306

AVerMedia®

www.avermedia.com
www.averdigi.com