11.Specifications

Camera type	1/2" or 1/3"	
System	NTSC	PAL
No. of pixels	510(H)X492(V)	500(H)X582(V)
H. Frequency	15.750KHZ	15.625KHZ
V. Frequency	59.9HZ	50HZ
Phase Angle	15mS=325°	17.5mS=315°
Sync. Power	60HZ±2HZ	50HZ±2HZ
Power Source	DC12V,AC24V,AC110V,AC230V	
Ele. Current	0.32A, 0.26A, 0.4A, 0.25A	
Ele. Shutter	Auto or Manual, 1/60～1/10000sec.	
Auto White Balance	Auto or Manual, 3200° ～8000° K	
Back light Compen.	ON/OFF(Only Auto Shutter Mode)	
AGC	ON/OFF(Manual Mode)	
Video Output	1.0Vp/p/75Ω BNC CONNECTOR	
Audio Output	2.0Vp-p 10K RCA CONNECTOR	
Min. Illumination	2.5Lux F1.2	
Resolution	330 Lines(center)	
S/N Ratio	32db, Standard 18db	
Lens Mount	C-mount or CS-mount	
Sync. System	Internal or line lock	
Working Temp	-10℃～+60℃	
Storage Temp	-30℃～+70℃	
Weight	DC12V=600g, AC24V=610g,AC110V=950g,AC230V=950g.	
Dimension	65(W)x55(H)x127(L)mm.	